

Mar resistant Tech-27512

Descriptions

Tech-27512 is a dispersion of high molecular weight silicone. It could provide excellent slip and release in water-born systems. It also could improve the anti-scratch performance of the coating film.

Physics and Chemical properties

Ingredient: Dispersion of high molecular weight silicone

Appearance: Viscous ointment liquid

Content: 80%

Solvent: Water

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★	★★★	★★★★★	★★★	★★★★★	★★★★★	★★★	★★★★★

★★★★★ Best ★ Worst

Application System and Dosage

Tech-27512 could be used in all *water borne* coatings.

Usually, it could be charged at random stage during the produce with **0.1%** to **1%** dosage to gross.

Package

18 kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

