

Silicone defoamer Tech-330

Description

Tech-330 is a universal organic silicone defoamer with great acceptant performance price ratio, excellent in compatibility, low possibility to cause crater, rapid defoaming speed and it could be used in any step of the manufacture of paint. It is suitable for epoxy and UV coating systems.

Physics and Chemical properties

Ingredient: Silicone with defoam compound

Appearance: Colorless to light yellow transparent liquid

Content: 7%

Solvent: Paraffin

Specialty

1. Tech-330 defoamer behavior in oil coating appears good compatibility.
2. Tech-330 defoamer is suitable for low viscosity epoxy system very much.
3. Tech-330 defoamer could provide outstanding defoam ability.

Application System and Dosage

TECH-330 is recommended to use in the *alkyd, acrylic, especial for epoxy and polyurethane* oil coating systems, as well as those solvent free systems.

Usually, it could be charged at random stage during the produce with **0.1% to 1%** dosage to gross.

Package

25kg pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel: 021-50796110 Fax: 021-50796113 Tel: 0757-22689820 Fax: 0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

