

Silicone defoamer Tech-386N

Description

Tech-386N is organic silicon antifoaming agent suitable for the solvent system has strong abilities to restrain and break the foam, meanwhile, very high efficiency which can realize good effect even under low dosage. Therefore, it's special for the coating and printing ink system with high viscosity to eliminate the tiny foam.

Physics and Chemical properties

Ingredient: Polysiloxane mixed with foam-breaking particles

Appearance: Opaque viscous liquid

Content: 100%

Specialty

1. Tech-386N is suitable for the solvent coating system has excellent abilities to restrain and break the foam.
2. Tech-386N is especially suitable for the system include pigment. It's necessary that estimate the compatibility before used in varnish system.
3. Tech-386N has extremely antifoaming efficiency, which can realize the extraordinary result only under few amount.

Application System and Dosage

Tech-386N could be used in the 2K epoxy system, PU system, radiation curing coating, solvent or radiation-curing silk screen ink system.

The dosage is **0.05% to 1%**

Package

25kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company –**

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company –**

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

