

Silicone defoamer Tech-319W

Description

Tech-319W is a organic silicone defoamer for water based systems. It has strong defoaming ability with low addition level. It should be introduced in grinding stage.

Physics and Chemical properties

Ingredient: modified Polydimethylsiloxane

Appearance: Colorless, viscous liquid

Content: 60%

Solvent: DPM

Specialty

1. Tech-319W defoamer is suit for water base and middle even high polarity oil coating systems, it could defoam as quickly as possible.
2. Tech-319W defoamer has the serious efficiency in defoam ability at the rather low level additive dosage, and appears very well.

Application System and Dosage

Tech-319W is recommended to use in the *middle and high polarity* oil coating systems, as well as water base system.

Usually, it should be charged at the lapping stage during the produce with **0.05%** to **1.0%** dosage to gross.

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

