

Silicone leveling agent Tech-UV2505

Describe

Tech-UV2505 is a modified silicone compound with acrylic double bond, which has excellent compatibility and leveling ability, and good anti-graffi effect. It is especially suitable for UV curing systems, and can also be used in water-based and solvent based paint systems to provide permanent hand feel.

Physical and chemical parameters

Component: acrylate modified polyether polysiloxane.

Appearance: yellow transparent liquid

Live fraction: 50%

Solvent: Tripropylene glycol diacrylate

Specificity

levelling	wetting	recoatibility	compatibility	Slippery	Low foam stability	Anti-crate r	Release effect
★★★★	★★★★	★	★★★★	★★★★★	★★	★★★★	★★★★

★★★★★★★ stands for the best ★ stands for the worst.

Application system and dosage

Tech-UV2505 is applicable to UV curing system

The addition amount varies according to different use systems, generally 0.1-1% of the total amount, and can be added at any stage of production.

Packaging

25kg steel pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

