

Substrate wetting agent Tech-2408

Description

Tech-2408 is polyether modified silicone with excellent substrate wetting for water-based and radiation curing system. It could also be used in agriculture application.

Physics and Chemical properties

Ingredient: Polyether Modified Silicone

Appearance: Light yellow transparent liquid

Content: 100%

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★	★★★★★	★★★★★	★★★★★	★	★★	★★★★★	★

Application System and Dosage

It's suitable for the water-wood-paint, industry water-borne coatings and UV-curable coatings, printing ink systems with *the pH value between 6 and 8*.

The amount is in terms of the different application system, around 0.1-1% of total in common. Tech-278 can be put in during any step of manufacture.

Package

25kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

