

Silicone defoamer Tech-3868

Description

Tech-3868 is organic silicon antifoaming agent suitable for the solvent system has strong abilities to restrain and break the foam. It's special for the coating and printing ink system with high viscosity to eliminate the tiny foam. Since the Tech-3868 has no solvent, thus it can be used in the system which is required has no solvent such as radiation-curing system or epoxy system.

Physics and Chemical properties

Ingredient: Polysiloxane mixed with foam-breaking particles

Appearance: Milk-white cloudy liquid

Content: 100%

Specialty

1. Tech-3868 is suitable for the solvent coating system has excellent abilities to restrain and break the foam.
2. Tech-3868 is especially suitable for the system include pigment. It's necessary that estimate the compatibility before used in varnish system.
3. Tech-3868 has extremely antifoaming efficiency, which can realize the extraordinary result only under few amount.

Application System and Dosage

Tech-3868 could be used in the 2K epoxy system, PU system, radiation curing coating, solvent or radiation-curing silk screen ink system. Please stir sufficiently to make sure the agent can disperse very well. Usually, it could be charged at random stage during the produce with **0.05%** to **1%** dosage to gross.

Package

25kg pail or 200kg drum

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel: 021-50796110 Fax: 021-50796113 Tel: 0757-22689820 Fax: 0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

