

Adhesion promoter Tech-7268

Descriptions

Tech-7268 is an adhesion promoter specifically developed for self-drying systems that enhances the adhesion of the paint film to metal substrates while improving the flexibility of the paint film

Physics and Chemical properties

Ingredient: Special polyester polymers

Appearance: Yellow solid

Content: 100%

Specialty

- ◆ Tech-7268 improves the adhesion of paint films to various difficult to adhere metals such as aluminum, zinc, stainless steel, and electroplated surfaces
- ◆ Tech-7268 increases the ductility and impact resistance of the paint film

Application System and Dosage

Tech-7268 can be used in a variety of self-drying systems, and the recommended dosage is 0.1%-5%, and can be added before and after.

Package

25kg plastic drum

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ Shanghai Company -

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ Guangdong Company -

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

