

Adhesion promoter Tech-7266-2

Description

Tech-7266-2 is a linear polyester with active hydrogen atoms adhesion promoter. It is suitable for self dry solvent coating systems. Tech-7266-2 has good compatibility with resin systems, and could improve the adhesion between the heat plastic paint film and metal substrate.

Physics and Chemical properties

Ingredient: Special polyester

Appearance: Colorless viscous transparent liquid

Content: 60%

Solvent: Disester mixture

Specialty

1. Tech-7266-2 adhesion promoter is suitable solvent self dry coating system to metal substrate.
2. Tech-7266-2 is a linear polyester with active hydrogen atom that could inhibit the aluminum powder to occur black.
3. Tech-7266-2 has good compatibility to heat plastic resins.

Application System and Dosage

TECH-7266-2 is recommended to use in the 1K solvent-based systems.

Usually, it could be charged at random stage during the produce with **0.1%** to **5%** dosage to gross.

Package

25kg plastic pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

