

Rheology modifier Tech-9010L

Description

Tech-9010L is a special polymeric rheology modifier with great anti-setting and anti-sagging ability. It has strong rheology and easy to introduce, suitable for all kinds of solvent-based systems to be used as anti-sagging and anti-setting agent. Take care the compatibility when using it in clear system.

Physics and Chemical properties

Ingredient: Solution of polyurea compound

Appearance: Light yellow transparent liquid

Content: 50%

Solvent: NMP

Specialty

1. Tech-9010L is proper for the solvent varnish system. It can rapid increase the viscosity and make the coating great in ability of anti-setting and anti-sagging.
2. Tech-9010L can used in baking systems without the unstable property with the mutative temperature.

Application System and Dosage

Tech-9010L is applied in all solvent base industry coating systems.

The amount is in terms of the different application system, around 0.1-0.7% of total in common when used as anti-setting agent and 0.5-3.0% as anti-sagging agent. Tech-9010 should be put in last step of manufacture.

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

