

Silicone-Free Leveling Agent Tech-115

Description

Tech-115 is a mixture of silicone-free surfactants. It is used in waterborne coating systems to prevent popping, cratering and improve leveling effect.

Physicochemical parameters

Composition: Mixture of silicone-free surfactants Appearance: Colorless transparent solution

Active content: 5%

Solvent: Dipropylene glycol monomethyl ether

Characteristics:

- 1. Tech-115 is widely applicable to waterborne coating and ink systems.
- 2. Tech-115 can prevent popping and cratering and does not contain APEO.

Application scope:

Used in waterborne coating and ink systems.

Recommended dosage:

Generally 0.1 - 1% of the total amount. It can be added at any stage in the production process.

Packaging: 25kg



A company focus on additives since its birth

■上海公司-

地址: 上海市浦东新区沪南公路 8666 弄上海智城 11 号楼 5 层

电话: 021-50796110 传真: 021-50796113

MSDS/TDS: www.tech-polymer.com.cn



啊: 本说明书的目的在于提供涂料、油墨等技术人员以基本产品信息, 仅供研发参考使用,不具有任何保证性质,请预先测试其适用性。



■广东公司-

地址:广东省佛山市顺德区勒流街道宝智园 1 栋 403 单元 电话: 0757-22689820 传真: 0757-22689270