

Rheological Modifier Tech-9430

Description

Tech-9430 is a polyurea compound and polyamide composite rheological agent, suitable for solvent-based and solvent-free coatings. After being mixed into the system, the additive will establish pseudoplasticity, thereby preventing sedimentation and sagging through thixotropy. It is widely used for anti-settling and anti-sagging of various industrial paints.

Physicochemical parameters

Composition: Polyurea-polyamide compound

Appearance: Light yellow viscous solution.

Active content: 50%

Solvent: N-methylpyrrolidone

Application system and dosage.

It is suitable for all kinds of solvent-based coating and ink systems.

The addition amount varies according to different application systems. For anti-settling, it is 0.1 - 0.7%. For anti-sagging, it is 0.5 - 3.0%. It is recommended to be added later.

Packaging: 25kg

TECH Polymer
A company focus on additives since its birth

■上海公司——

地址：上海市浦东新区沪南公路 8666 弄上海智城 11 号楼 5 层
电话：021-50796110 传真：021-50796113
MSDS/TDS: www.tech-polymer.com.cn

附：

本



在于提供涂料、油墨等技术人员以基本产品信息，
用，不具有任何保证性质，请预先测试其适用性。

■广东公司——

地址：广东省佛山市顺德区勒流街道宝智园 1 栋 403 单元
电话：0757-22689820 传真：0757-22689270