

Rheological additive Tech-9022W

Description

Tech-9022W is a water-based pre-dispersion based on organic synthetic amide wax. Due to its good dispersibility, it can be easily dispersed into the system, thus providing good rheological properties. It is widely used for anti sinking of primer and anti sagging of varnish.

physicochemical parameters

Composition: Polyamide wax dispersion

Appearance: yellow paste

Active ingredient: 20%

Solvent: water

Application system and dosage

Suitable for all kinds of water-based coatings, printing ink system, the amount of additive according to the different use of different systems, used as anti-settling: 0.5-2.0%, used as anti-sagging: 2.0-5.0

Packaging

18kg plastic pail

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

