

Leveling agent Tech-2762

Descriptions

Tech-2762 is polyether modified polysiloxane, it has excellent compatibility with most paint resins and has no reverse influence on recoatibility. It provide mar resistance for coating film and improve the gross of the paint film. Tech-2762 could be used in all kinds of systems.

Physics and Chemical properties

Ingredient : Polyether modified polysiloxane

Appearance: Light yellow viscous transparent liquid

Viscosity: 200-500mPaS

Content : 100%

Specialty

| Leveling | Wetting | Recoat Ability | Compatibility | Sliding | Low Foaming Stability | Anti-crater | Anti-adhesive |
|----------|---------|-------------------|---------------|---------|--------------------------|-------------|---------------|
| **** | **** | **** | **** | **** | **** | **** | *** |

 $\star \star \star \star \star$ Best \star Worst

Application System and Dosage

Tech-257N could be used in solvent-based and UV coatings as well as water borne coatings. Usually, it could be charged at random stage during the produce with 0.1% to 1% dosage to gross.

Package

25kg metal pail.



Notice The information provided does not constitute a contract to supply to any specification, or for any given application, and buyers should seek to verify their requirements and product use.

Tech Polymer Materials Co., Ltd. Shanghai China © 2013 Rm.602, Dehong Building, No. 665 Zhangjiang Road, Pudong Zone, Shanghai, 201203, China

∴ Fax: 86-21-50796113

* E-mail: johnson.tian@tech-polymer.com.cn