

Silicone defoamer Tech-330

Description

Tech-330 is a universal organic silicone defoamer with great acceptant performance price ratio, excellent in compatibility, low possibility to cause crater, rapid defoaming speed and it could be used in any step of the manufacture od paint. It is suitable for epoxy and UV coating systems.

Physics and Chemical properties

Ingredient : Silicone with defoam compound

Appearance: Colorless transparent liquid

Content: 7%

Solvent : Paraffin

Specialty

1. Tech-330 defoamer behavior in oil coating appears good compatibility.

2. Tech-330 defoamer is suitable for low viscosity epoxy system very much.

3. Tech-330 defoamer could provide outstanding defoam ability.

Application System and Dosage

TECH-330 is recommended to use in the *alkyd*, *acrylic*, *especial for epoxy* and *polyurethane* oil coating systems, as well as those solvent free systems.

Usually, it could be charged at random stage during the produce with 0.1% to 1% dosage to gross.

Package

25kg metal pail.



Notice The information provided does not constitute a contract to supply to any specification, or for any given application, and buyers should seek to verify their requirements and product use.

Tech Polymer Materials Co., Ltd. Shanghai China © 2013 Rm.602, Dehong Building, No. 665 Zhangjiang Road, Pudong Zone, Shanghai, 201203, China

∴ Tel: 86-21-50796110

∴ Fax: 86-21-50796113

* E-mail: johnson.tian@tech-polymer.com.cn