

Silicone-free defoamer Tech-4401

Description

Tech-4401 is a silicone-free defoamer. It is particularly suitable for systems such as saturated polyester, unsaturated polyester, epoxy, and UV curing. It has excellent compatibility and defoaming and air release capabilities.

Physics and Chemical properties

Ingredient: Mixture of non-silicon polymers

Appearance: Light yellow transparent liquid

Content: 100%

Specialty

1. Tech-4401 has remarkable air release ability.
2. Tech-4401 does not affect recoatability and has excellent compatibility

Application System and Dosage

Tech-4401 is particularly suitable for saturated polyester, unsaturated polyester, epoxy, UV curing and other systems.

For a total amount of 0.3 to 1.0%, please test the optimal dosage. After addition, it should be mixed under a sufficiently high shear force.

It is recommended to add it before grinding. The addition amount varies according to different application systems and can be added at any stage of production.

Package

25kg

TECH Polymer

A company focus on additives since its birth

■上海公司——

地址：上海市浦东新区沪南公路 8666 弄上海智城 11 号楼 5 层

电话：021-50796110 传真：021-50796113

MSDS/TDS: www.tech-polymer.com.cn

附：本说明书的目的在于提供涂料、油墨等技术人员以基本产品信息，仅供研发参考使用，不具有任何保证性质，请预先测试其适用性。



■广东公司——

地址：广东省佛山市顺德区勒流街道宝智园 1 栋 403 单元

电话：0757-22689820 传真：0757-22689270