

## Silicone-free defoamer Tech-4405

### Description

Tech-4405 is a silicone-free defoamer. It is particularly suitable for systems such as saturated polyester, unsaturated polyester, epoxy, and UV curing. It has excellent compatibility and defoaming and air release capabilities.

### Physics and Chemical properties

**Ingredient:** Mixture of non-silicon polymers

**Appearance:** Light yellow transparent liquid

**Content:** 100%

### Specialty

1. Tech-4405 has remarkable air release ability.
2. Tech-4405 does not affect recoatability and has excellent compatibility

### Application System and Dosage

Tech-4405 is particularly suitable for saturated polyester, unsaturated polyester, epoxy, UV curing and other systems.

For a total amount of 0.3 to 1.0%, please test the optimal dosage. After addition, it should be mixed under a sufficiently high shear force.

It is recommended to add it before grinding. The addition amount varies according to different application systems and can be added at any stage of production.

### Package

25kg

### TECH Polymer

A company focus on additives since its birth

#### ■上海公司——

地址：上海市浦东新区沪南公路 8666 弄上海智城 11 号楼 5 层

电话：021-50796110 传真：021-50796113

MSDS/TDS: [www.tech-polymer.com.cn](http://www.tech-polymer.com.cn)

附：本说明书的目的在于提供涂料、油墨等技术人员以基本产品信息，仅供研发参考使用，不具有任何保证性质，请预先测试其适用性。



#### ■广东公司——

地址：广东省佛山市顺德区勒流街道宝智园 1 栋 403 单元

电话：0757-22689820 传真：0757-22689270