

## Mar resistant Tech-2482N

### Descriptions

Tech-2482N is a dispersion of high molecular weight modified silicone. It could provide excellent slip and release in water-born systems. It also could improve the anti-scratch performance of the coating film.

### Physics and Chemical properties

**Ingredient:** dispersion of high molecular weight silicone

**Appearance:** white emulsion

**Content:** 60%

**Solvent:** Water

### Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★	★★★	★★★★★	★★★	★★★★★	★★★★★	★★★	★★★★★

★★★★★ Best ★ Worst

### Application System and Dosage

Tech-2482 could be used in all *water borne* coatings.

Usually, it could be charged at random stage during the produce with **0.1%** to **1%** dosage to gross.

### Package

25kg plastic pail.

## TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

#### ■ Shanghai Company –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

#### ■ Guangdong Company –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: [www.tech-polymer.com.cn](http://www.tech-polymer.com.cn)

