

## Silicone defoamer Tech-371W

### Description

Tech-371W is a organic silicone defoamer for water based systems. It has strong defoaming ability with low addition level. It should be introduced in grinding stage.

### Physics and Chemical properties

**Ingredient:** Modified polysiloxane mixed with foam-breaking substance

**Appearance:** Light yellow turbid viscous liquid

**Content:** 100%

### Specialty

1. Tech-371W defoamer is suit for water base and middle even high polarity oil coating systems, it could defoam as quickly as possible.
2. Tech-371W defoamer has the serious efficiency in defoam ability at the rather low level additive dosage, and appears very well.

### Application System and Dosage

Tech-371W is recommended to use in the *middle and high polarity* oil coating systems, as well as water base system.

Usually, it should be charged at the lapping stage during the produce with **0.05%** to **1.0%** dosage to gross.

### Package

25kg metal pail.

## TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel: 021-50796110 Fax: 021-50796113 Tel: 0757-22689820 Fax: 0757-22689270

MSDS/TDS: [www.tech-polymer.com.cn](http://www.tech-polymer.com.cn)

