

Polymeric defoamer Tech-4390

Description

Tech-4390 is polymeric antifoaming agent suitable for solvent-based system. It can eliminate the bubble from manufacture and application and it has no reverse effect on the adhesion between inter-coating film.

Physics and Chemical properties

Ingredient: Acrylic polymer

Appearance: Light yellow transparent liquid

Content: 50%

Solvent: Solvent naphtha

Specialty

1. Tech-4390 has strong antifoaming capacity and could be used in all kinds of solvent-based systems
2. Tech-4390 has no influence the adhesion and re-coating

Application System and Dosage

Tech-4390 could be used in PU-2K, amino baking varnish, nitro dip-coating, acid cure amino, coil coating systems.

The recommended amount is around 0.1~1.0%

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

