

Silicone-Free Defoamer Tech-4823

Description

Tech-4823 is a silicone-free defoamer. It is suitable for systems such as saturated polyester, unsaturated polyester, polyurethane, epoxy, and UV curing. It has good compatibility and defoaming and air release capabilities.

Physics and Chemical properties

Ingredient: Silicone-Free Polymer

Appearance: Light yellow transparent liquid

Content: 100%

Specialty

1. Tech-4823 has remarkable air release ability.
2. Tech-4823 does not affect recoatability.

Application System and Dosage

Suitable for systems such as saturated polyester, unsaturated polyester, polyurethane, epoxy, and UV curing.

For a total amount of 0.3 to 1.0%, please test the optimal dosage. After addition, it should be mixed under a sufficiently high shear force. It is recommended to add it before grinding. The addition amount varies according to different application systems and can be added at any stage of production.

Package

25kg

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

