

Polymeric defoamer Tech-49202

Description

Tech-49202 is non-silicon antifoaming agent which is special designed for the radiation-curing coating system. The Tech-49202 has excellent compatibility with good defoaming and antifoaming abilities. It has no influence on the re-coating.

Physics and Chemical properties

Ingredient: None-silicone polymers

Appearance: Brown viscous liquid

Content: 100%

Specialty

1. Tech-49202 has excellent compatibility in radiation-curing system. Also, Tech-420 can be used in the other thermosetting resin system such as unsaturated polyester.
2. Tech-49202 has very good recoatability for avoiding of curtain breaking during curtain coating in photocurable coating system.

Application System and Dosage

Tech-49202 could be used in the radiation-curing system, unsaturated polyester system.

The dosage can be around 0.3-1.0% of total, please test the optimized dosage. It's suggested that add the Tech-49202 before grinding, and the mixture should be under sufficient strong shear force after add the agent.

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

