

Leveling agent Tech-UV2021N

Descriptions

Tech-UV2021N is modified polysiloxane with acrylic group, it has good compatibility with most paint resins and it could provide good leveling and slip in UV systems.

Physics and Chemical properties

Ingredient: Polyether modified polysiloxane with acrylic group

Appearance: Light yellow viscous transparent liquid

Content: 100%

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
****	****	****	****	****	**	****	***

★★★★ Best ★ Worst

Application System and Dosage

Tech-UV2021N could be used in UV coatings.

Usually, it could be charged at random stage during the produce with 0.1% to 1% dosage to gross.

Package

25kg metal pail.



A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance

Shanghai Company -

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■Guangdong Company -

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province. Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270 MSDS/TDS: www.tech-polymer.com.cn

