

Leveling agent Tech-UV2022N

Descriptions

Tech-UV2022N is polyether modified polysiloxane with acrylic group , it has excellent compatibility with most paint resins and it could provide excellent leveling and slip in UV systems.

Physics and Chemical properties

Ingredient: Polyether modified polysiloxane with acrylic group

Appearance: Light yellow viscous transparent liquid

Content: 100%

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★★★	★★★★	★★★★★	★★★★★	★★★★★	★★	★★★★	★★★★

★★★★★ Best ★ Worst

Application System and Dosage

Tech-UV2022N could be used in UV coatings.

Usually, it could be charged at random stage during the produce with **0.1%** to **1%** dosage to gross.

Package

25kg metal pail.

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

