

Anti-graffiti additive Tech-UV2029

Description

Tech-UV2029 is a modified silicone compound with acrylic double bonds, which can participate in the cross-linking of UV systems, which is used to improve the anti-blocking and anti-graffiti properties of the system, while providing excellent slip

Physics and Chemical properties

Ingredient: Acrylate-modified polysiloxane

Appearance: Clear to translucent viscous liquid

Content: 100%

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★	★★	★★	★★	★★★★★	★★★★★	★★★★★	★★★★★

★★★★★Best ★ Worst

Application System and Dosage

Tech-UV2029 is suitable for light-curing systems.

The dosage is different according to different use systems, generally 0.1-1% of the total amount, which can be added at any stage of production.

Package

25kg iron drum

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ Shanghai Company -

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ Guangdong Company -

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

