

## Dispersant Tech-5240N

### Description

Tech-5240N is a polymeric dispersant powder suitable for organic pigment especially dispersion in medium polarity solvent borne and UV coating systems. It has good compatibility with many kinds of resin, suitable for all kinds of pigment and filler, and with strong dispersing power and excellent store stability.

### Physics and Chemical properties

**Ingredient:** Copolymer with pigment affinity group

**Appearance:** Yellow powder

**Content:** 100%

### Specialty

1. Tech-5240N dispersant suitable for all kinds of pigment dispersion in medium polarity solvent borne coating systems, especially for organic pigment such as **HPP** and with good compatibility.
2. Tech-5240N is polymeric dispersant with strong dispersing power and excellent store stability.
3. Tech-5240N dispersant suitable for those organic pigments hard to disperse in high solid content because of it could decrease the viscosity effectively.

### Application System and Dosage

Tech-5240N is recommended to use in medium polarity solvent borne and UV coating systems.

Usually, it should be charged before the grind stage during the produce, with **10%** to **15%** to inorganic pigment, **5%** to **6%** to TiO<sub>2</sub>, **30%** to **50%** dosage to organic pigment, **50%** to **100%** to carbon black.

### Package

**25kg** metal pail.

## TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: [www.tech-polymer.com.cn](http://www.tech-polymer.com.cn)

