

# **Dispersant Tech-598**

### **Description**

Tech-598 is a dispersant with acid group and it is suitable for inorganic pigments in water-based, solvent -based and UV curing systems. It could decrease the viscosity and improve the pigments loading.

### Physics and Chemical properties

**Ingredient:** Copolymer with pigment affinity group

**Appearance:** Light yellow viscous liquid

Content: 100%

#### **Specialty**

- 1. Tech-598 has excellent compatibility with many kinds of resins.
- 2. Tech-598 could decrease the mill viscosity and it could increase the pigment content in the color paste.

### **Application System and Dosage**

Tech-598 is suitable for both water-based and solvent-based systems.

Usually, it should be charged before the grind stage during the produce, with 1% to 5% to other inorganic pigment, with 2% to 4% to  $TiO_2$ .

## **Package**

25kg plastic pail.



A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance

Shanghai Company -

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai Guangdong Company -

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province. Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

