

## **Dispersant Tech-6018**

### **Description**

Tech-6018 is a polymeric dispersing agent with star type structure. It has excellent wetting ability for many kinds of pigments. It could greatly decrease the mill viscosity and it increase the pigment content in the color paste.

#### **Physics and Chemical properties**

**Ingredient:** Block copolymer with pigment affinity group

Appearance: Yellow viscous liquid

**Content:** 100%

### **Specialty**

- 1. Tech-6018 is suitable for middle-polar systems and has excellent compatibility with many kinds of resins
- 2. Tech-6018 could greatly decrease the mill viscosity and it could increase the pigment content in the color paste.

# **Application System and Dosage**

Tech-6018 is suitable for middle-polar resin systems and is specially suitable for UV systems.

Usually, it should be charged before the grind stage during the produce, with 10% to 15% to inorganic pigment, 5% to 6% to  $TiO_2$ , 30% to 90% dosage to organic pigment, 70% to 100% dosage to carbon black.

### **Package**

25kg plastic pail.



A company focus on additives since its birth

MSDS/TDS: www.tech-polymer.com.cn

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

Shanghai Company -

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai 

Guangdong Company -

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province. Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

