

# **Dispersant Tech-6310**

# **Description**

Tech-6310 is macromolecule hyper-dispersant and it has excellent wetting disperse ability to the various organic pigments. It can decrease the grinded system viscosity and increase the fill of pigments. Meanwhile, it has super anti-flocculation ability thus improve the storage stability of grinded color paste.

#### Physics and Chemical properties

**Ingredient**: Block copolymer of macromolecular with acidic groups

Appearance: Brown transparent liquid

Content: 50%

**Solvent:** mixed dibasic esters

#### **Specialty**

- 1. Tech-6310 is suitable for the medium polarity system has good compatibility with the common coating resin and the popularity in the coating system.
- 2. Tech-6310 has excellent ability to improve the storage stability tremendously of grinded color paste.
- 3. Tech-6310 is very suitable to disperse matting agent and improve its store stablility.

## **Application System and Dosage**

Tech-6310 is suitable for the 2K PU, alkyd, acrylate, polyester, amino baking varnish and UV system Usually, it should be charged before the grind stage during the produce, with 10% to 15% to inorganic pigment, with 30% to 90% to organic pigment, with 70% to 100% to carbon black.

## **Package**

25kg metal pail.



**Notice** The information provided does not constitute a contract to supply to any specification, or for any given application, and buyers should seek to verify their requirements and product use.