

Wetting Agent Tech-2846

Description

Tech-2846 is a polyether modified organosilicon compound that can greatly reduce the surface tension of the system, providing strong wetting ability without affecting recoating properties. It is an excellent substrate wetting leveling agent suitable for water-based wood coatings, inks, and photopolymerization systems, with defoaming properties.

Physical and chemical parameters

Ingredients: Polyether modified silicone oil
Appearance: Light yellow transparent solution
Active ingredient: 50%
Solvent: Dipropylene glycol monomethyl ether

Feature

Leveling property	Wetting force	Recoating property	Compatibility	Slippery degree	Low stability foam	Anti shrinkage porosity	Anti adhesion property
★★★★★	★★★★★	★★★★★	★★★★	★	★★★★	★★★★★	★

★★★★★ Representing the Best ★ Representing the worst

Application system and usage

Suitable for water-based wood coatings, water-based industrial coatings, UV curable coatings, inks and other systems;

The amount of addition varies according to different usage systems, generally ranging from 0.1% to 1% of the total amount, and can be added at any stage of production.

Packing

25KG

TECH Polymer

A company focus on additives since its birth

■上海公司——

地址：上海市浦东新区沪南公路 8666 弄上海智城 11 号楼 5 层
 电话：021-50796110 传真：021-50796113
 MSDS/TDS: www.tech-polymer.com.cn

附：本说明书的目的在于提供涂料、油墨等技术人员以基本产品信息，仅供研发参考使用，不具有任何保证性质，请预先测试其适用性。



■广东公司——

地址：广东省佛山市顺德区勒流街道宝智园 1 栋 403 单元
 电话：0757-22689820 传真：0757-22689270