

Substrate wetting agent Tech-24316

Description

Tech-24316 is polyether modified fluoro compound. It can greatly decrease the surface tension and provide the strength wetting ability and without any influence on the recoat ability. It is proper for the aqueous wood lacquer, printing ink and radiation curing systems.

Physics and Chemical properties

Ingredient: Polyether Modified Fluoro compound

Appearance: Light yellow transparent liquid

Content: 25%

Solvent: Diethylene glycol monobutyl ether

Specialty

Leveling	Wetting	Recoat Ability	Compatibility	Sliding	Low Foaming Stability	Anti-crater	Anti-adhesive
★★★★★	★★★★★	★★★★★	★★★★★	★	★★	★★★★★	★

Application System and Dosage

It's suitable for the water-wood-paint, industry water-borne coatings and UV-curable coatings, printing ink systems.

The amount is in terms of the different application system, around 0.1-1% of total in common. Tech-24316 can be put in during any step of manufacture.

Package

25kg plastic pail

TECH Polymer

A company focus on additives since its birth

For research and development purposes only, there is no warranty of any kind, so please test its suitability in advance.

■ **Shanghai Company** –

Address: 5th Floor, Building 11, Shanghai Zhi Cheng, Lane 8666, Hunan Road, Pudong New Area, Shanghai

■ **Guangdong Company** –

Address: Unit 403, Building 1, Baozhi Garden, Leliu Street, Shunde District, Foshan City, Guangdong Province.

Tel:021-50796110 Fax:021-50796113 Tel:0757-22689820 Fax:0757-22689270

MSDS/TDS: www.tech-polymer.com.cn

